
FLUX ROUND ADJUSTABLE RECESSED

INDOOR / DOWNLIGHT







Size XS Installation Method Adjustable Recessed Dimensions (mm) Ø110mmx140mm Cutout Size (mm) Ø102mm Accessories Without Accessory IP Rating IP20	PHYSICAL	
Dimensions (mm) Ø110mmx140mm Cutout Size (mm) Ø102mm Accessories Without Accessory IP Rating IP20	Size	XS
Cutout Size (mm) Ø102mm Accessories Without Accessory IP Rating IP20	Installation Method	Adjustable Recessed
Accessories Without Accessory IP Rating IP20	Dimensions (mm)	Ø110mmx140mm
IP Rating IP20	Cutout Size (mm)	Ø102mm
•	Accessories	Without Accessory
	IP Rating	IP20
Finish Textured White	Finish	Textured White
Tilt Angle 25°	Tilt Angle	25°

l	







ELECTRICAL	
Wattage	10W
Forward Current	250mA
Voltage	240V
Dimming Control	Phase-Cut Dimmable

IP20

OPTICAL	
Optic	Reflector
Distribution	Wide 33°
ССТ	3000K
CRI	CRI90
System Lumen	669lm
System Efficacy	67lm/W
Light Output Ratio	70
Lifetime (L70B50)	50000hrs

ADDITIONAL	
LED Module	Standard Tridonic SLE G7
LED Driver	Remote
Warranty	3 Years

Order Code: ADN82AR01.930STW.10W1001

Flux XS Round Adj Rec Downlight White CRI90 3000K 669lm 33° 10W 250mA Phase-Cut Dim