
FLUX TRIPLE ADJUSTABLE RECESSED

INDOOR / DOWNLIGHT







| PHYSICAL | |
|---------------------|---------------------|
| Size | S |
| Installation Method | Adjustable Recessed |
| Dimensions (mm) | 444mmx140mmx172mm |
| Cutout Size (mm) | 430mmx130mm |
| Accessories | Without Accessory |
| IP Rating | IP20 |
| Finish | Textured White |
| Tilt Angle | 24° |

| ELECTRICAL | |
|-----------------|--------------------|
| Wattage | 60W |
| Forward Current | 500mA |
| Voltage | 240V |
| Dimming Control | Phase-Cut Dimmable |















IP20

| OPTICAL | |
|--------------------|------------|
| Optic | Reflector |
| Distribution | Medium 24° |
| ССТ | 3000K |
| CRI | CRI90 |
| System Lumen | 4968lm |
| System Efficacy | 83lm/W |
| Light Output Ratio | 70 |
| Lifetime (L70B50) | 50000hrs |

| ADDITIONAL | |
|------------|--------------------------|
| LED Module | Standard Tridonic SLE G7 |
| LED Driver | Remote |
| Warranty | 3 Years |

Order Code: ADN88AR01.930STM.60W1001

Flux S Triple Adj Rec Downlight White CRI90 3000K 4968lm 24° 3x20W 500mA Phase-Cut Dim