


ANDRO FLEX SUSPENDED

INDOOR / PENDANT

ambience

MAKING LIGHT WORK



PHYSICAL

| | |
|---------------------|-------------------|
| Size | S |
| Installation Method | Flex Suspended |
| Dimensions (mm) | Ø62mm x 172mm |
| Accessories | Without Accessory |
| IP Rating | IP20 |
| Finish | Textured White |

ELECTRICAL

| | |
|-----------------|--------------------|
| Wattage | 15W |
| Forward Current | 350mA |
| Voltage | 240V |
| Dimming Control | Phase-Cut Dimmable |



RoHS



IP20

O P T I C A L

| | |
|--------------------|------------|
| Optic | Lens |
| Distribution | Medium 23° |
| CCT | 3000K |
| CRI | CRI90 |
| System Lumen | 1277lm |
| System Efficacy | 85lm/W |
| Light Output Ratio | 80 |
| Lifetime (L70B50) | 50,000hrs |

A D D I T I O N A L

| | |
|------------|--------------------------|
| LED Module | Standard Tridonic SLE G7 |
| LED Driver | Integral |
| Warranty | 5 Years |

Order Code: APN01SU01.930STM.15W1001

Andro S Sus Flex 2m Pendant Textured White CRI90 3000K 1277lm 23° 15W Phase-Cut Dim SM Canopy