


# ROLL ADJUSTABLE SURFACE MOUNTED

INDOOR / SPOTLIGHT

ambience

MAKING LIGHT WORK



## PHYSICAL

|                     |                            |
|---------------------|----------------------------|
| Size                | XS                         |
| Installation Method | Adjustable Surface Mounted |
| Dimensions (mm)     | Ø65mm x 178.5mm            |
| Accessories         | Without Accessory          |
| IP Rating           | IP20                       |
| Finish              | White                      |
| Rotate Angle        | 355°                       |
| Tilt Angle          | 90°                        |

## ELECTRICAL

|                 |                    |
|-----------------|--------------------|
| Wattage         | 12W                |
| Forward Current | 300mA              |
| Voltage         | 240V               |
| Dimming Control | Phase-Cut Dimmable |



**RoHS**



**IP20**

## O P T I C A L

|                    |            |
|--------------------|------------|
| Optic              | Reflector  |
| Distribution       | Medium 24° |
| CCT                | 3000K      |
| CRI                | CRI90      |
| System Lumen       | 1058lm     |
| System Efficacy    | 88lm/W     |
| Light Output Ratio | 85         |
| Lifetime (L70B50)  | 50000hrs   |

## A D D I T I O N A L

|            |                          |
|------------|--------------------------|
| LED Module | Standard Tridonic SLE G7 |
| LED Driver | Integral                 |
| Warranty   | 3 Years                  |

---

Order Code: **ASP09AS01.930STM.12W1001**

Roll XS Adj SM Spot White CRI90 3000K 1058lm 24° 12W Phase-Cut Dim