
## ABACO SEMI-RECESSED

INDOOR / DOWNLIGHT







| PHYSICAL            |                   |
|---------------------|-------------------|
| Size                | S                 |
| Installation Method | Semi-Recessed     |
| Dimensions (mm)     | Ø200mmx53mm       |
| Cutout Size (mm)    | Ø164mm            |
| Accessories         | Without Accessory |
| IP Rating           | IP20              |
| Finish              | Textured White    |















| ELECTRICAL      |              |
|-----------------|--------------|
| Wattage         | 28W          |
| Forward Current | 700mA        |
| Voltage         | 240V         |
| Dimming Control | Non-Dimmable |

**IP20** 

| OPTICAL            |            |
|--------------------|------------|
| Optic              | Diffuser   |
| Distribution       | Flood 109° |
| ССТ                | 3000K      |
| CRI                | CRI80      |
| System Lumen       | 1940lm     |
| System Efficacy    | 69lm/W     |
| Light Output Ratio | 80         |
| Lifetime (L70B50)  | 50000hrs   |

| ADDITIONAL |           |
|------------|-----------|
| LED Module | SMD Seoul |
| LED Driver | Integral  |
| Warranty   | 3 Years   |

Order Code: BDN33SR01.930SMF.28W0001

Abaco S Semi-Rec Downlight White CRI80 3000K 1940Im 109° 28W 700mA Non-Dim