
## CRIO R ADJUSTABLE RECESSED

INDOOR / DOWNLIGHT







PHYSICAL	
Installation Method	Adjustable Recessed
Dimensions (mm)	Ø50x32mm; Cut-out Ø40mm
Cutout Size (mm)	Ø40mm
Accessories	Without Accessory
IP Rating	IP40
Finish	Textured White
Rotate Angle	360°
Tilt Angle	30°









ELECTRICAL	
Wattage	2W
Forward Current	500mA
Voltage	2.5-3V (Vf)
Dimming Control	All dimming types (driver to be ordered separately)







**IP40** 

OPTICAL	
Optic	Lens
Distribution	Wide 36°
ССТ	3000K
CRI	CRI90
System Lumen	155lm
System Efficacy	78lm/W
Light Output Ratio	80
Lifetime (L70B50)	50,000hrs

ADDITIONAL	
LED Module	Nichia
LED Driver	Remote
Warranty	2 Years
Add-Ons	IK06 Rated

Order Code: BDN61AR01.930NIW.02WX701

Crio R Adj Rec Downlight White CRI90 3000K 155 $\mathrm{Im}\ 36^{\circ}\ 2\mathrm{W}\ 500\mathrm{mA}\ \mathrm{Without}\ \mathrm{Driver}\ \mathrm{IP40}$