


BENDABLE MEDLEY SURFACE / CONCEALED

INDOOR / LINEAR

ambience

MAKING LIGHT WORK



PHYSICAL

Installation Method	Surface/Concealed
Dimensions (mm)	16x15mmx1000mm; Cuttable anywhere
Accessories	End feed 3M FIG8 single end
IP Rating	IP20

ELECTRICAL

Wattage	9W/m
Voltage	24V
Dimming Control	All types (order separately)



RoHS



IP20

O P T I C A L

Distribution	Flood 120°
CCT	3000K
CRI	CRI90
System Lumen	380lm/m
System Efficacy	42lm/W
Lifetime (L70B50)	50,000hrs(indoor); 36,000hrs(outdoor)

A D D I T I O N A L

LED Module	SMD2835 120LEDs/m
LED Driver	Remote
Warranty	3 Years
Add-Ons	Dual Bend; Minimum bending radius is 60mm; Max. length is 10m with power at single end and 20m with power at both ends; Also available in IP44 option.

Order Code: BLIS08FS16.0930F.09W0001

Bendable Medley Fix SM 16mm CRI90 3000K 120° 120LEDs/m 380lm/m 9W/m 24V IP20 Free Cut End feed 3M FIG8 single end (plastic EC)