


BENDABLE MEDLEY SURFACE / CONCEALED

INDOOR / LINEAR

ambience

MAKING LIGHT WORK



PHYSICAL

| | |
|---------------------|-----------------------------------|
| Installation Method | Surface/Concealed |
| Dimensions (mm) | 16x15mmx1000mm; Cuttable anywhere |
| Accessories | End feed 3M FIG8 single end |
| IP Rating | IP20 |

ELECTRICAL

| | |
|-----------------|------------------------------|
| Wattage | 9W/m |
| Voltage | 24V |
| Dimming Control | All types (order separately) |



RoHS



O P T I C A L

| | |
|-------------------|---------------------------------------|
| Distribution | Flood 120° |
| CCT | 3000K |
| CRI | CRI90 |
| System Lumen | 380lm/m |
| System Efficacy | 42lm/W |
| Lifetime (L70B50) | 50,000hrs(indoor); 36,000hrs(outdoor) |

IP20**A D D I T I O N A L**

| | |
|------------|--|
| LED Module | SMD2835 120LEDs/m |
| LED Driver | Remote |
| Warranty | 3 Years |
| Add-Ons | Dual Bend; Minimum bending radius is 60mm; Max. length is 10m with power at single end and 20m with power at both ends; Also available in IP44 option. |

Order Code: BLIS08FS16.0930F.09W0001

Bendable Medley Fix SM 16mm CRI90 3000K 120° 120LEDs/m 380lm/m 9W/m 24V IP20 Free Cut End feed 3M FIG8 single end (plastic EC)