


BENDABLE PICCOLO IP SURFACE/CONCEALED

OUTDOOR / LINEAR

ambience

MAKING LIGHT WORK




PHYSICAL

Installation Method	Surface/Concealed
Dimensions (mm)	8.5x10mmx1000mm; Cuttable anywhere
Accessories	End feed 1M WP+DC CON single end
IP Rating	IP65

ELECTRICAL

Wattage	9W/m
Voltage	24V
Dimming Control	All types (order separately)



RoHS



IP65

O P T I C A L

Distribution	Flood 120°
CCT	3000K
CRI	CRI90
System Lumen	266lm/m
System Efficacy	30lm/W
Lifetime (L70B50)	50,000hrs(indoor); 36,000hrs(outdoor)

A D D I T I O N A L

LED Module	SMD2835 120LEDs/m
LED Driver	Remote
Warranty	3 Years
Add-Ons	Side Bend; Minimum bending radius is 100mm; Max. length is 10m with power at single end and 20m with power at both ends.

Order Code: BLIS09FS09.0930F.09W0201

**Bendable Piccolo Fix SM 8.5mm CRI90 3000K 120° 120LEDs/m 266lm/m 9W/m 24V IP65 Free Cut
End feed 1M WP+DC CON single end (extrusion EC)**