


# BENDABLE PICCOLO IP SURFACE / CONCEALED

OUTDOOR / LINEAR

ambience

MAKING LIGHT WORK



## PHYSICAL

Installation Method	Surface/Concealed
Dimensions (mm)	8.5x10mmx1000mm; Cuttable every 50mm
Accessories	End feed 1M WP+DC CON single end
IP Rating	IP65

## ELECTRICAL

Wattage	9W/m
Voltage	24V
Dimming Control	All types (order separately)



**RoHS**



**O P T I C A L**

Distribution	Flood 120°
CCT	3000K
CRI	CRI90
System Lumen	266lm/m
System Efficacy	30lm/W
Lifetime (L70B50)	50,000hrs(indoor); 36,000hrs(outdoor)

**IP65****A D D I T I O N A L**

LED Module	SMD2835 120LEDs/m
LED Driver	Remote
Warranty	3 Years
Add-Ons	Minimum bending radius is 100mm; Max. length is 10m with power at single end and 20m with power at both ends.

---

**Order Code: BLIS09FS09.0930F.09W0201**

Bendable Piccolo Fix SM 8.5mm CRI90 3000K 120° 120LEDs/m 266lm/m 9W/m 24V IP65 Cut 50mm  
End feed 1M WP+DC CON single end (extrusion EC)