

VIRTUOSO IP SURFACE / SUSPENDED

OUTDOOR / LINEAR

ambience

MAKING LIGHT WORK



PHYSICAL

Installation Method	Surface/Suspended
Dimensions (mm)	Ø22mmx1000mm; Cuttable every 35.71mm
Accessories	End feed 1M WP+DC CON single end
IP Rating	IP65

ELECTRICAL

Wattage	20W/m
Voltage	24V
Dimming Control	All types (order separately)



RoHS



O P T I C A L

Distribution	Flood 360°
--------------	------------

CCT	3000K
-----	-------

CRI	CRI90
-----	-------

System Lumen	950lm
--------------	-------

System Efficacy	48lm/W
-----------------	--------

Lifetime (L70B50)	36,000hrs
-------------------	-----------

IP65**A D D I T I O N A L**

LED Module	SMD2835 168LEDs/m
------------	-------------------

LED Driver	Remote
------------	--------

Warranty	3 Years
----------	---------

Add-Ons	Dual Bend; Minimum bending radius is Ø75mm; Max. length is 5m with power at single end
---------	----------------------------------------------------------------------------------------

Order Code: BLIS10FS22.0930F.20W0201

Virtuoso Surface/Sus Ø21M WP+DC CONm CRI90 3000K 360° 168LEDs/m 170lm/W 2x10W/m 24V
IP65 End feed 1M WP+DC CON single end (sealed EC)