


BENDABLE SERENADE IP SURFACE/ CONCEALED

OUTDOOR / LINEAR

ambience

MAKING LIGHT WORK



PHYSICAL

Installation Method	Fixed Surface Mounted
Dimensions (mm)	23x23mmx1000mm; Cuttable every 250mm
Accessories	Bottom feed 1M WP+DC CON single end
IP Rating	IP67
Finish	White

ELECTRICAL

Wattage	18W/m
Voltage	24V
Dimming Control	All types (order separately)



RoHS



IP67

O P T I C A L

Distribution	Medium 30°
CCT	3000K
CRI	CRI90
System Efficacy	0lm/W
Lifetime (L70B50)	50,000hrs(indoor); 36,000hrs(outdoor)

A D D I T I O N A L

LED Module	SMD3030 24LEDs/m
LED Driver	Remote
Warranty	3 Years
Add-Ons	Minimum bending radius is 180mm; Max. length is 10m with power at single end and 20m with power at both ends. Also available in IP67 option.

Order Code: BLIS56FS23.0930M.18W0403.WH

Bendable Serenade Fix SM 23mm White CRI90 3000K 30° 24LEDs/m 90lm/W 18W/m 24V IP67 Cut 250mm Bottom feed 1M WP+DC CON single end (diecast EC)