


MEDLEY SURFACE / CONCEALED

INDOOR / LINEAR

ambience

MAKING LIGHT WORK



PHYSICAL

Installation Method	Surface/Concealed
Accessories	Male/Female connector 2M, Open single end tail 3M, Custom
IP Rating	IP20
Finish	Textured White, Textured Black, Textured Silver, Custom

ELECTRICAL

Wattage	5W/m, 10W/m, 14.5W/m, 15W/m, 19.2W/m, 20W/m, 22W/m
Voltage	24V
Dimming Control	All types (order separately)



RoHS



O P T I C A L


Optic	Clear, Frost, Opal, Smoked
Distribution	Flood 120°
CCT	1600K, 1800K, 2000K, 2200K, 2400K, 2700K, 3000K, 3500K, 4000K, 6500K, Amber, Blue, Cyan, Dim to Warm 1800K-3000K, Green, RGB, RGBW+1600K, RGBW+2700K, RGBW+3000K, RGBW+3500K, RGBW+4000K, RGBW+5000K, RGBW+6500K, Red, Tunable 1800K-3000K, Tunable 2700K-6500K
CRI	CRI80, CRI90
System Lumen	30lm - 1127lm
System Efficacy	Up to 68lm/W
Lifetime (L70B50)	50,000hrs

A D D I T I O N A L

LED Module	Boost 8mm, Boost 10mm, Boost Colour 10mm, Boost Dim to Warm 12mm, Boost RGB 10mm, Boost RGBW 12mm, Boost Tunable WH 10mm, Boost Ultra Warm 10mm
LED Driver	Remote
Warranty	5 Years
Add-Ons	Suitable for concealed mounting



IP20



Medley