

OLIO SQUARE ADJUSTABLE RECESSED

CREATE / DOWNLIGHT

ambience

MAKING LIGHT WORK



PHYSICAL

Size	XS, S, M
Installation Method	Adjustable Recessed
Cutout Size (mm)	45mm x 45mm, 68mm x 68mm, 96mm x 96mm
Accessories	Honeycomb Louvre, Without Accessory
IP Rating	IP20
Finish	Textured White, Textured Black, Custom
Rotate Angle	355°
Tilt Angle	30°
Anti-Glare Ring Finish	Textured Black, Custom
Secondary Reflector Finish	Matt, Textured White, Textured Black, Specular, Chrome, Gold, Custom

ELECTRICAL

Wattage	6W, 9W, 13W, 15W, 21W
Forward Current	250mA, 350mA, 500mA
Voltage	240V
Dimming Control	1-10V Dimmable, DALI Dimmable, Phase-Cut Dimmable

MEDIUM



NARROW



WIDE



FLOOD



CE

RoHS

O P T I C A L


Optic	Lens, Reflector
Distribution	Medium / Narrow / Wide / Flood
CCT	2700K, 3000K, 4000K
CRI	CRI90
System Lumen	365lm - 1150lm
System Efficacy	Up to 69lm/W
Light Output Ratio	85
Lifetime (L70B50)	50,000hrs

A D D I T I O N A L


LED Module	CREE, Citizen
LED Driver	Remote
Warranty	5 Years




IP20



Olio XS Square



Olio S Square



Olio M Square